

# COMMERCIAL VEHICLE TIRES

## Truck and Bus Tires - Radial Ply - Tire Load Limits at Various Cold Inflation Pressures

**NOTE:**

Never Exceed the Wheel Manufacturer's Maximum Pressure Limitation  
 Always Use Approved Tire and Rim Combinations for Diameters and Contours  
 Exceeding the Legal Speed Limit is Neither Recommended nor Endorsed

S = Single Configuration, or 2 Tires per Axle

D = Dual Configuration, or 4 Tires per Axle

Letter in Parenthesis Indicate Load Range At The Designated Max Load/Max Pressure Combination

WHEEL DIAMETER 17.5"															
	PSI	70	75	80	85	90	95	100	105	110	112	115	120	125	130
		kPa	480	520	550	585	620	*655/660	690	725	760	775	790	*825/830	860
205/65R17.5 LR J 132/130	LBS SINGLE			2975	3120	3275	3440	3560	3705	3845		3970	4135	4255	4410 (J)
	LBS DUAL			5130	5380	3110	3270	3385	3520	3660		3775	3925	4040	4190 (J)
	KG SINGLE			1350	1415	1485	1560	1615	1680	1745		1800	1875	1930	2000 (J)
R02 Pro Trailer	KG DUAL			1280	1315	1410	1480	1535	1595	1660		1710	1780	1830	1900 (J)
205/75R17.5 LR G 124/122	LBS SINGLE	2245	2600	2725	2865	3000	3155	3265	3395	3525 (G)					
	LBS DUAL	2285	2440	2550	2865	2810	2955	3060	3185	3305 (G)					
	KG SINGLE	1110	1180	1235	1300	1360	1430	1480	1540	1600 (G)					
R02 Profuel Steer	KG DUAL	1035	1105	1155	1215	1275	1340	1385	1445	1500 (G)					
215/75R17.5 LR G 128/126	LBS SINGLE	2745	2930	3065	3220	3375	3550	3670	3825	3970 (G)					
		2595	2765	2895	3040	3185	3345	3465	3610	3750 (G)					
	KG SINGLE	1245	1330	1390	1460	1530	1610	1665	1735	1800 (G)					
R02 Profuel Steer	KG DUAL	1175	1255	1310	1380	1445	1515	1570	1635	1700 (G)					
215/75R17.5 LR J 136/134	LBS SINGLE			3330	3495	3670	3860	3990	4155	4310		4455	4630	4760	4940 (J)
	LBS DUAL			5720	6010	3465	3650	3780	3930	4085		4210	4380	4510	4675 (J)
	KG SINGLE			1510	1585	1665	1750	1810	1885	1955		2020	2100	2160	2240 (J)
R02 Pro Trailer	KG DUAL			1430	1500	1570	1655	1715	1780	1850		1910	1985	2045	2120 (J)
235/75R17.5 LR G 132/130 R02 Profuel Steer	LBS SINGLE	3010	3210	3350	3515	3695	3880	4025	4180	4345	4410 (G)				
	LBS DUAL	5180	3040	3185	3345	3505	3680	3820	3975	4125	4190 (G)				
	KG SINGLE	1365	1455	1520	1595	1675	1760	1825	1895	1970	2000 (G)				
	KG DUAL	1295	1380	1445	1520	1590	1670	1735	1805	1870	1900 (G)				
235/75R17.5 LR J 245/70R17.5 LR J 143/141 R02 Profuel Steer	LBS SINGLE				4200	4410	4615	4820	5025	5225		5420	5620	5810	6010 (J)
	LBS DUAL				3970	4170	4365	4555	4745	4935		5125	5310	5495	5680 (J)
	KG SINGLE				1910	2020	2100	2200	2280	2360		2470	2550	2650	2725 (J)
	KG DUAL				1800	1900	1980	2080	2160	2230		2330	2410	2500	2575 (J)

## WHEEL DIAMETER 19.5"

	PSI	70	75	80	85	90	95	100	105	110	112	115	120	125	130
	kPa	480	520	550	585	620	*655/660	690	725	760	775	790	*825/830	860	900
225/70R19.5 LR G 128/126 R02 Profuel Steer, R02 Pro Trailer	LBS SINGLE			3195	3315	3450	3640	3715	3845	3970 (G)					
	LBS DUAL			3000	3115	3245	3415	3490	3615	3750 (G)					
	KG SINGLE			1450	1500	1570	1650	1690	1740	1800 (G)					
	KG DUAL			1360	1410	1470	1550	1580	1640	1700 (G)					
245/70R19.5 LR G 140/138 R02 Profuel Steer, R02 Profuel Drive	LBS SINGLE				3750	3925	4100	4270	4440	4610		4775	4940 (H)		
	LBS DUAL				3550	3715	3880	4040	4200	4360		4520	4675 (H)		
	KG SINGLE				1700	1770	1860	1930	2000	2090		2150	2240 (H)		
	KG DUAL				1610	1680	1760	1830	1890	1980		2040	2120 (H)		
215/75R17.5 LR G 128/126 R02 Profuel Steer	LBS SINGLE				4430	4610	4850	5025	5190	5425	5510 (G)				
	LBS DUAL				4180	4355	4575	4740	4905	5120	5205 (G)				
	KG SINGLE				2010	2090	2200	2280	2355	2460	2500 (G)				
	KG DUAL				1895	1975	2075	2150	2225	2320	2360 (G)				
215/75R17.5 LR J 136/134 R02 Pro Trailer	LBS SINGLE				4895	5095	5345	5545	5765	5995		6185	6425	6615 (H)	
	LBS DUAL				4570	4750	4990	5175	5385	5595		5775	6000	6175 (H)	
	KG SINGLE				2220	2310	2425	2515	2615	2720		2805	2915	3000 (H)	
	KG DUAL				2070	2155	2265	2345	2440	2535		2615	2720	2800 (H)	
235/75R17.5 LR J 245/70R17.5 LR J 143/141 R02 Profuel Steer	LBS SINGLE					5480	5765	5975	6215	6450		6660	6925		7390 (J)
	LBS DUAL					5150	5415	5615	5840	6065		6225	6510		6945 (J)
	KG SINGLE					2485	2615	2710	2820	2925		3020	3140		3350 (J)
	KG DUAL					2335	2455	2545	2650	2750		2835	2950		3150 (J)

## WHEEL DIAMETER 22.5"

	PSI	70	75	80	85	90	95	100	105	110	112	115	120	125	130
	kPa	480	520	550	590	620	*655/660	690	720	760	775	790	*825/830	860	900
11R22.5 LR G 144/141  H89 Evo Drive, H94 Drive, H89 Trailer	LBS SINGLE	4530	4770	4990	5220	5510	5730	5950	6175 (G)						
	LBS DUAL	4380	4580	4760	4950	5205	5415	5625	5840 (G)						
	KG SINGLE	2050	2160	2260	2370	2500	2600	2700	2800 (G)						
	KG DUAL	1990	2080	2160	2250	2360	2460	2560	2650 (G)						
11R22.5 LR H 146/143  H89 Evo, R89, G02 On Off Multiaxle, R89 Drive, R89 CS Drive, G02 On Off Drive	LBS SINGLE			4990	5220	5510	5730	5950	6175	6320		6465	6610 (H)		
	LBS DUAL			4760	4950	5205	5415	5625	5840	5895		5950	6005 (H)		
	KG SINGLE			2260	2370	2500	2600	2700	2800	2870		2940	3000 (H)		
	KG DUAL			2160	2250	2360	2460	2560	2650	2680		2710	2725 (H)		
12R22.5 LR L 152/148  G02 On Off Multiaxle, FR:01, TR:01, G02 On off Drive	LBS SINGLE				5785	6020	6340	6560	6825	7090		7310	7605	7830 (J)	
	LBS DUAL				5135	5345	5620	5820	6055	6285		6485	6750	6945 (J)	
	KG SINGLE				2625	2730	2875	2975	3095	3215		3315	3450	3550 (J)	
	KG DUAL				2330	2425	2550	2640	2745	2850		2940	3060	3150 (J)	
295/60R22.5 LR J 150/147  FH01 Energy, R02 Proway Drive	LBS SINGLE				5270	5480	5765	5975	6175	6450		6660	6925	7120	7390 (J)
	LBS DUAL				4830	5030	5290	5475	5670	5920		6105	6355	6535	6780 (J)
	KG SINGLE				2390	2485	2615	2710	2800	2925		3020	3140	3230	3350 (J)
	KG DUAL				2190	2280	2400	2485	2570	2685		2770	2880	2965	3075 (J)
295/75R22.5 LR G 144/141  H89 Evo Drive, H94 Drive, H89 Trailer	LBS SINGLE	4500	4940	4940	5155	5370	5510	5780	5980	6175 (G)					
		4095	4540	4540	4690	4885	5070	5260	5440	5675 (G)					
	KG SINGLE	2040	2240	2240	2340	2440	2500	2620	2710	2800 (G)					
		1860	2060	2060	2130	2220	2300	2390	2470	2575 (G)					
295/80R22.5 LR J 152/148  MC01, FR01, TR01, R02 Proway Drive	LBS SINGLE				5785	6020	6340	6560	6825	7090		7310	7605	7830 (J)	
					5135	5345	5620	5820	6055	6285		6845	6750	6945 (J)	
	KG SINGLE				2625	2730	2875	2975	3095	3215		3315	3450	3550 (J)	
					2330	2425	2550	2640	2747,5	2852,5		2940	3060	3150 (J)	
295/80R22.5 LR J 156/149  FH01 Coach	LBS SINGLE			6160	6525	6790	7130	7395	7695	7990		8235	8575	8820 (J)	
	LBS DUAL			5010	5300	5515	5795	6005	6250	6490		6695	6965	7170 (J)	
	KG SINGLE			2795	2960	3080	3235	3355	3490	3625		3735	3890	4000 (J)	
	KG DUAL			2270	2405	2500	2630	2725	2835	2945		3035	3160	3250 (J)	

## WHEEL DIAMETER 22.5"

	PSI	70	75	80	85	90	95	100	105	110	112	115	120	123	125
	kPa	480	520	550	590	620	*655/660	690	720	760	775	790	*825/830	850	860
295/75R22.5 LR H 149/146  H89 Evo, R89, R89 Drive, R89 CS Drive	LBS SINGLE			5060	5350	5570	5850	6060	6270	6550		6760	7030	7160 (H)	
	LBS DUAL			4670	4940	5140	5400	5600	5790	6050		6240	6490	6610 (H)	
	KG SINGLE			2295	2425	2525	2655	2750	2845	2970		3065	3190	3250 (H)	
	KG DUAL			2118	2240	2330	2450	2540	2628	2743		2830	2943	3000 (H)	
295/80R22.5 LR J 154/149  R02 Proway Steer, U02 Urban-e Pro Multiaxle	LBS SINGLE			5830	6130	6430	6760	7000	7280	7560		7790	8110	8270 (J)	
	LBS DUAL			9180	5310	5570	5850	6060	6310	6550		6760	7030	7160 (J)	
	KG SINGLE			2645	2780	2915	3065	3175	3300	3430		3535	3680	3750 (J)	
	KG DUAL			2295	2410	2525	2655	2750	2860	2970		3065	3185	3250 (J)	

## WHEEL DIAMETER 22.5"

	PSI	70	75	80	85	90	95	100	105	110	112	115	120	125	130
	kPa	480	520	550	590	620	*655/660	690	720	760	775	790	*825/830	860	900
275/70R22.5 LR H 140/137  FH15	LBS SINGLE			4190	4370	4550	4675	4895	5065	5205		5400	5510 (H)		
	LBS DUAL			3970	4110	4275	4410	4455	4610	4675		4915	5070 (H)		
	KG SINGLE			1900	1980	2060	2120	2220	2300	2360		2450	2500 (H)		
	KG DUAL			1800	1860	1940	2000	2020	2090	2120		2230	2300 (H)		
**275/70R22.5 LR J 148/145  R89	LBS SINGLE						5420	5610	5810	6060		6260	6500	6640	6940 (J)
	LBS DUAL						4990	5170	5350	5580		5760	5990	6110	6395 (J)
	KG SINGLE						2460	2545	2635	2750		2840	2950	3010	3150 (J)
	KG DUAL						2260	2345	2425	2530		2610	2715	2770	2900 (J)
**275/70R22.5 LR J 152/148  U02 Urban-e Pro Multiaxle	LBS SINGLE			5280	5580	5810	6110	6330	6550	6830		7060	7330	7550	7830 (J)
	LBS DUAL			8500	8990	5150	5420	5620	5810	6070		6260	6510	6700	6940 (J)
	KG SINGLE			2395	2530	2635	2770	2870	2970	3100		3200	3325	3425	3550 (J)
	KG DUAL			2125	2245	2335	2455	2545	2635	2750		2835	2950	3035	3150 (J)
315/80R22.5 LR J 156/150  TG01	LBS SINGLE				6525	6790	7130	7395	7650	7990		8235	8575	8820 (J)	
	LBS DUAL				5460	5680	5975	6195	6405	6690		6900	7175	7390 (J)	
	KG SINGLE				2960	3080	3235	3355	3470	3625		3735	3890	4000 (J)	
	KG DUAL				2480	2580	2710	2810	2905	3035		3130	3255	3350 (J)	
315/80R22.5 LR L 158/156  H94 Coach, R89, R89 Drive	LBS SINGLE						7310	7570	7840	8180		8440	8790	8950	9370 (L)
	LBS DUAL						6880	7130	7370	7710		7950	8270	8420	8820 (L)
	KG SINGLE						3315	3435	3555	3710		3830	3985	4060	4250 (L)
	KG DUAL						3120	3235	3345	3495		3605	3750	3820	4000 (L)
315/80R22.5 LR L 161/157  MG89, FG01	LBS SINGLE						7960	8250	8530	8910		9180	9560	9740	10200 (L)
	LBS DUAL						7090	7350	7610	7940		8200	8520	8690	9090 (L)
	KG SINGLE						3610	3740	3870	4040		4165	4335	4420	4625 (L)
	KG DUAL						3215	3335	3450	3600		3715	3865	3940	4125 (L)
385/55R22.5 LR L 164K - SINGLE ONLY R02 Pro Trailer	LBS SINGLE			7430	7860	8180	8600	8920	9230	9620		9930	10330	10630	11000 (L)
	LBS DUAL														
	KG SINGLE			3370	3565	3710	3900	4045	4185	4365		4505	4685	4820	5000 (L)
	KG DUAL														
385/65R22.5 LR L 164K - SINGLE ONLY G02 PRO, R02 Pro Trailer	LBS SINGLE			7860	8180	8600	8920	9230	9625		9930	10330	10630	11025 (L)	
	KG SINGLE			3565	3710	3900	4045	4185	4365		4505	4685	4820	5000 (L)	
425/65R22.5 LR L 165 K - SINGLE ONLY G02 PRO	LBS SINGLE			8640	9000	9450	9790	10130	10580		10910	11400 (L)			
	KG SINGLE			3920	4080	4285	4440	4595	4800		4950	5150 (L)			

## WHEEL DIAMETER 24.5"

	PSI	70	75	80	85	90	95	100	105	110	112	115	120	125	130
	kPa	480	520	550	590	620	*655/660	690	720	760	775	790	*825/830	860	900
11R24.5 LR H 149/146 R89, R89 CS Drive, H89 Trailer, GO2 On Off Multi-axle	LBS SINGLE				5550	5840	6095	6350	6610	6790		6970	7160 (H)		
	LBS DUAL				5260	5510	5675	5840	6005	6205		6405	6610 (H)		
	KG SINGLE				2520	2650	2770	2890	3000	3080		3160	3250 (H)		
	KG DUAL				2390	2500	2580	2660	2725	2820		2910	3000 (H)		
285/75R24.5 LR H 147/144 R89, R89 CS Drive	LBS SINGLE				5210	5450	5675	5835	6040	6175		6440	6780 (H)		
	LBS DUAL				4740	4930	5205	5310	5495	5675		5860	6175 (H)		
	KG SINGLE				2360	2460	2575	2650	2740	2800		2920	3075 (H)		
	KG DUAL				2150	2240	2360	2410	2490	2575		2660	2800 (H)		

\* The First Number Reflects the Official Conversion and the Second Number Reflects the Previous Value. Some Products May Still Be Marked With The Previous Value.

\*\* 275/70R22.5 LR J can only be used on either 7.50" or 8.25" wheel. It cannot be used on 9" wheel.

\*\*\* 295/60R22.5 LR J can only be used on either 9.00" or 9.75" wheel. It cannot be used on 8.25 wheel.

## WHEEL DIAMETER 20" TUBELESS

	PSI	70	75	80	85	90	95	100	105	110	112	115	120	125	130
	kPa	480	520	550	590	620	*655/660	690	720	760	775	790	*825/830	860	900
335/80R20 LR H 149 PS22-PISTA	LBS SINGLE	5560	5920	6200	6550	6810	7170 (H)								
	LBS DUAL														
	KG SINGLE	2520	2685	2810	2970	3090	3250 (H)								
	KG DUAL														
365/80R20 G 152 PS22-PISTA	LBS SINGLE	6390	6800	7110	7520	7830 (G)									
	LBS DUAL														
	KG SINGLE	2895	3085	3225	3410	3550 (G)									
	KG DUAL														
1400R20 LR M 164/160 SO2-PISTA	LBS SINGLE	7630	8140	8510	9010	9370	9840	10210	10560	11025 (M)					
	LBS DUAL	6870	7330	7660	8100	8430	8860	9180	9500	9925 (M)					
	KG SINGLE	3460	3690	3860	4085	4250	4465	4630	4790	5000 (M)					
	KG DUAL	3115	3325	3475	3675	3820	4020	4165	4310	4500 (M)					

## WHEEL DIAMETER 20" TUBELESS

	PSI	70	75	80	85	90	95	100	105	110	112	115	120	125	130
	kPa	480	520	550	590	620	*655/660	690	720	760	775	790	*825/830	860	900
365/85R20 LR J 164 PS22-PISTA	LBS SINGLE		7580	7930	8390	8730	9170	9510	9830	10270		10600	11025 (J)		
	LBS DUAL														
	KG SINGLE		3440	3595	3805	3960	4160	4315	4460	4660		4805	5000 (J)		
	KG DUAL														
395/85R20 LR HJ 168 PS22-PISTA	LBS SINGLE			8630	9140	9500	9990	10350	10710	11190		11530	12000	12350 (J)	
	LBS DUAL														
	KG SINGLE			3915	4145	4310	4530	4695	4860	5075		5230	5445	5600 (J)	
	KG DUAL														

## WHEEL DIAMETER 24" TUBE TYPE

	PSI	70	75	80	85	90	95	100	105	110	112	115	120	125	130
	kPa	480	520	550	590	620	*655/660	690	720	760	775	790	*825/830	860	900
1200R24TT LR L 160/156 FG85, TG85, TQ:01	LBS SINGLE				7340	7640	8025	8325	8610	8985		9270	9645	9925 (L)	
	LBS DUAL				6525	6790	7140	7400	7650	7985		8240	8570	8820 (L)	
	KG SINGLE				3330	3465	3640	3775	3905	4075		4205	4375	4500 (L)	
	KG DUAL				2960	3080	3240	3355	3470	3625		3740	3890	4000 (L)	

\* The First Number Reflects the Official Conversion and the Second Number Reflects the Previous Value. Some Products May Still Be Marked With the Previous Value.

# LOAD TABLES FOR TRUCKS, BUSES AND TRAILER USED IN NORMAL HIGHWAY SERVICE

Loads are indicated per axle

**NOTE:**  
 Never Exceed the Wheel Manufacturer's Maximum Pressure Limitation  
 Always Use Approved Tire and Rim Combinations for Diameters and Contours  
 Exceeding the Legal Speed Limit is Neither Recommended nor Endorsed  
 S = Single Configuration, or 2 Tires per Axle  
 D = Dual Configuration, or 4 Tires per Axle

WHEEL DIAMETER 17.5"																
	PSI	70	75	80	85	90	95	100	105	110	112	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL
	kPa	480	520	550	585	620	*655/660	690	720	760	775	790	*825/830	860	900	
205/65R17.5 LR J 132/130	LBS SINGLE			5950	6240	6550	6880	7120	7410	7690		7940	8510	8510	8820	S 4410 LBS AT 130 PSI
	LBS DUAL			20520	21520	12440	13080	13540	14080	14640		15100	5070 (H)		16760	D 4190 LBS AT 130 PSI
R02 Pro Trailer	KG SINGLE			2700	2830	2970	3120	3230	3360	3490		3600	16160	3860	4000	S 2000 KG AT 900 kPa
	KG DUAL			5120	5380	5640	5920	6140	6380	6640		6840	3860	7320	7600	D 1900 KG AT 900 kPa
205/75R17.5 LR G 124/122	LBS SINGLE	4890	5200	5450	5730	6000	6310	6530	6790	7050			7320	1610		S 3525 LBS AT 110 PSI
	LBS DUAL	9140	9760	10200	10740	11240	11820	12240	12740	13220						D 3305 LBS AT 110 PSI
R02 Profuel Steer	KG SINGLE	2220	2360	2470	2600	2720	2860	2960	3080	3200						S 1600 KG AT 760 kPa
	KG DUAL	4140	4420	4620	4860	5100	5360	5540	5780	6000						D 1500 KG AT 760 kPa
215/75R17.5 LR G 128/126	LBS SINGLE	5490	5860	6130	6440	6750	7100	7340	7650	7940						S 3970 LBS AT 110 PSI
	LBS DUAL	10380	11060	11580	12160	12740	13380	13860	14440	15000						D 3750 LBS AT 110 PSI
R02 Profuel Steer	KG SINGLE	2490	2660	2780	2920	3060	3220	3330	3470	3600						S 1800 KG AT 760 kPa
	KG DUAL	4700	5020	5240	5520	5780	6060	6280	6540	6800						D 1700 KG AT 760 kPa
215/75R17.5 LR J 136/134	LBS SINGLE			6660	6990	7340	7720	7980	8310	8620		8910	9260	9520	9880	S 4940 LBS AT 130 PSI
	LBS DUAL			22880	24040	13860	14600	15120	15720	16340		16840	17520	18040	18700	D 4675 LBS AT 130 PSI
R02 Pro Trailer	KG SINGLE			3020	3170	3330	3500	3620	3770	3910		4040	4200	4320	4480	S 2240 KG AT 900 kPa
	KG DUAL			5720	6000	6280	6620	6860	7120	7400		7640	7940	8180	8480	D 2120 KG AT 900 kPa
235/75R17.5 LR J 132/130	LBS SINGLE	6020	6420	6700	7030	7390	7760	8050	8360	8690	8820					S 4410 LBS AT 112 PSI
	LBS DUAL	20720	12160	12740	13380	14020	14720	15280	15900	16500	16760					D 4190 LBS AT 112 PSI
R02 Profuel Steer	KG SINGLE	2730	2910	3040	3190	3350	3520	3650	3790	3940	4000					S 2000 KG AT 775 kPa
	KG DUAL	5180	5520	5780	6070	6360	6680	6930	7210	7480	7600					D 1900 KG AT 775 kPa
235/75R17.5 LR J 245/70R17.5 LR J 143/141	LBS SINGLE				8400	8820	9230	9460	10050	10450		10840	11240	11620	12020	S 6010 LBS AT 130 PSI
	LBS DUAL				15880	16680	17460	18220	18980	19740		20500	21240	21980	22720	D 5680 LBS AT 130 PSI
R02 Pro Trailer	KG SINGLE				3820	4040	4200	4400	4560	4720		4940	5100	5300	5450	S 2725 KG AT 900 kPa
	KG DUAL				7200	7600	7920	8320	8640	8920		9320	9640	10000	10300	D 2575 KG AT 900 kPa

## WHEEL DIAMETER 19.5"

	PSI	70	75	80	85	90	95	100	105	110	112	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL
	kPa	480	520	550	585/590	620	*655/660	690	720	760	775	790	*825/830	860	900	
225/70R19.5 LR G 128/126 R02 Profuel Steer, R02 Profuel Drive	LBS SINGLE	9060	9540	9980	6630	6900	7280	7430	7690	7940						S 3970 LBS AT 110 PSI
	LBS DUAL			6390	12460	12980	13600	13960	14460	15000						D 3750 LBS AT 110 PSI
	KG SINGLE			12000	3000	3140	3300	3380	3480	3600						S 1800 KG AT 760 kPa
	KG DUAL			2900	5640	5880	6200	6320	6560	6800						D 1700 KG AT 760 kPa
245/70R19.5 LR H 136/134 R02 Profuel Steer, R02 Profuel Drive	LBS SINGLE			5440	7500	7850	8200	8540	8880	9220		9550	9800			S 4940 LBS AT 120 PSI
	LBS DUAL				14200	14860	15520	16160	16800	17440		18080	18700			D 4675 LBS AT 120 PSI
	KG SINGLE				3400	3540	3720	3860	4000	4180		4300	4480			S 2240 KG AT 825 kPa
	KG DUAL				6400	6720	7040	7320	7560	7920		8160	8480			D 2120 KG AT 825 kPa
265/70R19.5 LR G 140/138 R02 Profuel Steer, R02 Profuel Drive	LBS SINGLE				8860	9220	9700	10050	10380	10850	11010					S 5510 LBS AT 112 PSI
	LBS DUAL				16720	17420	18300	18960	19620	20480	20820					D 5205 LBS AT 112 PSI
	KG SINGLE				4020	4180	4400	4560	4710	4920	5000					S 2500 KG AT 775 kPa
	KG DUAL				7580	7900	8300	8600	8900	9280	9440					D 2360 KG AT 775 kPa
285/70R19.5 LR H 146/144 R02 Profuel Steer, R02 Profuel Drive	LBS SINGLE				9790	10190	10690	11090	11530	11990		12370	12850	13230		S 6615 LBS AT 125 PSI
	LBS DUAL				18280	19000	19960	20700	21540	22380		23100	24000	24700		D 6175 LBS AT 125 PSI
	KG SINGLE				4440	4620	4850	5030	5230	5440		5610	5830	6000		S 3000 KG AT 850 kPa
	KG DUAL				8280	8620	9060	9380	9760	10140		10460	10880	11200		D 2800 KG AT 860 kPa
285/70R19.5 LR J 150/148 R02 Pro Trailer	LBS SINGLE					10960	11530	11950	12430	12900		13320	13850		14780	S 7390 LBS AT 130 PSI
	LBS DUAL					20600	21160	22460	23360	24260		25020	26040		27780	D 6945 LBS AT 130 PSI
	KG SINGLE					4970	5230	5420	5640	5850		6040	6280		6700	S 3350 KG AT 900 kPa
	KG DUAL					9340	9820	10180	10600	11000		11340	11800		12600	D 3150 KG AT 900 kPa

## WHEEL DIAMETER 22.5"

	PSI	70	75	80	85	90	95	100	105	110	112	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL
	kPa	480	520	550	590	620	*655/660	690	720	760	775	790	*825/830	860	900	
11R22.5 LR G 144/141 H89 Evo Drive, H94 Drive, H89 Trailer	LBS SINGLE	9060	9540	9980	10440	11020	11460	11900	12350							S 6175 LBS AT 105 PSI
	LBS DUAL	17250	18320	19040	19800	20820	21660	22500	23360							D 5840 LBS AT 105 PSI
	KG SINGLE	4100	4320	4520	4740	5000	5200	5400	5600							S 2800 KG AT 720 kPa
	KG DUAL	7960	8320	8640	9000	9440	9840	10240	10600							D 2650 KG AT 720 kPa
11R22.5 LR H 146/143 H89 Evo, R89, G02 On Off Multi-axle, R89 Drive R89 CS Drive, G02 On Off Drive	LBS SINGLE		9540	9980	10440	11020	11460	11900	12350	12640		12930	13220			S 6610 LBS AT 120 PSI
	LBS DUAL		18320	19040	19800	20820	21660	22500	23360	23580		23800	24020			D 6005 LBS AT 120 PSI
	KG SINGLE		4320	4520	4740	5000	5200	5400	5600	5740		5880	6000			S 3000 KG AT 830 kPa
	KG DUAL		8320	8640	9000	9440	9840	10240	10600	10720		10840	10900			D 2725 KG AT 830 kPa
12R22.5 LR J 152/148 G02 On Off Multi-axle, FR:01, TR:01, G02 On Off Drive	LBS SINGLE				11570	12040	12680	13120	13650	14180		14620	15210	15660		S 7830 LBS AT 125 PSI
	LBS DUAL				20540	21380	22480	23280	24220	25140		25940	27000	27780		D 6945 LBS AT 125 PSI
	KG SINGLE				5250	5460	5750	5950	6190	6430		6630	6900	7100		S 3550 KG AT 860 kPa
	KG DUAL				9320	9700	10200	10560	10980	11400		11760	12240	12600		D 3150 KG AT 860 kPa
***295/60R22.5 LR J 150/147 FH01 Energy, R02 Proway drive	LBS SINGLE				10540	10960	11530	11950	12350	12900		13320	13850	14240	14780	S 7390 LBS AT 130 PSI
	LBS DUAL				19320	20120	21160	21900	22680	23680		24420	25420	26140	27120	D 6780 LBS AT 130 PSI
	KG SINGLE				4780	4970	5230	5420	5600	5850		6040	6280	6460	6700	S 3350 KG AT 900 kPa
	KG DUAL				8760	9120	9600	9940	10280	10740		11080	11520	11860	12300	D 3075 KG AT 900 kPa
295/75R22.5 LR G 144/141 H89 Evo Drive, H94 Drive, H89 Trailer	LBS SINGLE	9000	9450	9880	10310	10740	11020	11560	11960	12350						S 6175 LBS AT 110 PSI
	LBS DUAL	16380	17200	18160	18760	19540	20280	21040	21760	22700						D 5675 LBS AT 110 PSI
	KG SINGLE	4080	4280	4480	4680	4880	5000	5240	5420	5600						S 2800 KG AT 760 kPa
	KG DUAL	7440	7800	8240	8520	8880	9200	9560	9880	10300						D 2575 KG AT 760 kPa
295/80R22.5 LR J 152/148 MC01, FR01, TR01, R02 Proway Drive	LBS SINGLE				11570	12040	12680	13120	13650	14180		14620	15210	15660		S 7830 LBS AT 125 PSI
	LBS DUAL				20540	21380	22480	23280	24220	25140		25940	27000	27780		D 6945 LBS AT 125 PSI
	KG SINGLE				5250	5460	5750	5950	6190	6430		6630	6900	7100		S 3550 KG AT 860 kPa
	KG DUAL				9320	9700	10200	10560	10990	11410		11760	12240	12600		D 3150 KG AT 860 kPa
295/80R22.5 LR J 156/149 FH01 Coach	LBS SINGLE			12320	13050	13580	14260	14790	15390	15980		16470	17150	17640		S 8820 LBS AT 125 PSI
	LBS DUAL			20040	21200	22060	23180	24020	25000	25960		26780	27860	28680		D 7170 LBS AT 125 PSI
	KG SINGLE			5590	5920	6160	6470	6710	6980	7250		7470	7780	8000		S 4000 KG AT 860 kPa
	KG DUAL			9080	9620	10000	10520	10900	11340	11780		12140	12640	13000		D 3250 KG AT 860 kPa

## WHEEL DIAMETER 22.5"

	PSI	70	75	80	85	90	95	100	105	110	112	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL
	kPa	480	520	550	590	620	*655/660	690	720	760	775	790	*825/830	860	900	
295/75R22.5 LR H 149/146 H89 Evo, R89, R89 Drive, R89 CS Drive	LBS SINGLE			10120	10700	11140	11700	12120	12540	13100		13520	14060	14320		S 7160 LBS AT 123 PSI
	LBS DUAL			18680	19760	20560	21600	22400	23160	24200		24960	25960	26440		D 6610 LBS AT 123 PSI
	KG SINGLE			4590	4850	5050	5310	5500	5690	5940		6130	6380	6500		S 3250 KG AT 850 kPa
	KG DUAL			8472	8960	9320	9800	10160	10512	10972		11320	11772	12000		D 3000 KG AT 850 kPa
295/80R22.5 LR J 154/149 R02 Proway Steer, U02 Urban-e Pro Multi-axle	LBS SINGLE			11660	12260	12860	13520	14000	14560	15120		15580	16220	16540		S 8270 LBS AT 123 PSI
	LBS DUAL			36720	21240	22280	23400	2420	25240	26200		27040	28120	28640		D 7160 LBS AT 123 PSI
	KG SINGLE			5290	5560	5830	6130	6350	6600	6860		7070	7360	7500		S 3750 KG AT 850 kPa
	KG DUAL			9180	9640	10100	10620	11000	11440	11880		12260	12740	13000		D 3250 KG AT 850 kPa

## WHEEL DIAMETER 22.5"

	PSI	70	75	80	85	90	95	100	105	110	112	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL
	kPa	480	520	550	590	620	*655/660	690	720	760	775	790	*825/830	860	900	
255/70R22.5 LR H 140/137 FH15	LBS SINGLE			8380	8740	9100	9530	9790	10130	10410		10800	11020			S 5510 LBS AT 120 PSI
	LBS DUAL			15880	16440	17100	17640	17820	18440	18700		19660	20280			D 5070 LBS AT 120 PSI
	KG SINGLE			3800	3960	4120	4240	4440	4600	4720		4900	5000			S 2500 KG AT 830 kPa
	KG DUAL			7200	7440	7760	8000	8080	8360	8480		8920	9200			D 2300 KG AT 830 kPa
**275/70R22.5 LR J 148/145 R89	LBS SINGLE						10840	11220	11620	12120		12520	13000	13280	13880	S 6940 LBS AT 130 PSI
	LBS DUAL						19960	20680	21400	22320		23040	23960	24440	25580	D 6395 LBS AT 130 PSI
	KG SINGLE						4920	5090	5270	5500		5680	5900	6020	6300	S 3150 KG AT 900 kPa
	KG DUAL						9040	9380	9700	10120		10400	10860	11080	11600	D 2900 KG AT 900 kPa
**275/70R22.5 LR J 152/1458 U02 Urban-e Pro Multiaxle	LBS SINGLE			10560	11160	11620	12220	12660	13100	13660		14120	14660	15100	15660	S 7830 LBS AT 130 PSI
	LBS DUAL			34000	35960	20600	21680	22480	23240	24280		25040	26040	26800	27760	D 6940 LBS AT 130 PSI
	KG SINGLE			4790	5060	5270	5540	5740	5940	6200		6400	6650	6850	7100	S 3550 KG AT 900 kPa
	KG DUAL			8500	8980	9340	9820	10180	10540	11000		11340	11800	12140	12600	D 3150 KG AT 900 kPa
315/80R22.5 LR J 156/150 TG01	LBS SINGLE				13050	13580	14260	14790	15300	15980		16470	17150	17640		S 8820 KG AT 125 PSI
	LBS DUAL				21840	22720	23900	24780	25620	26760		27600	28700	29560		D 7390 LBS AT 125 PSI
	KG SINGLE				5920	6160	6470	6710	6940	7250		7470	7780	8000		S 4000 KG AT 860 kPa
	KG DUAL				9910	10310	10840	11240	11620	12140		12520	13020	13400		D 3350 KG AT 860 kPa
315/80R22.5 LR L 158/156 H94 Coach, R89, R89 Drive	LBS SINGLE						14620	15140	15680	16360		16880	17580	17900	18740	S 9370 LBS AT 130 PSI
	LBS DUAL						27520	28520	29480	30840		31800	33080	33680	35280	D 8820 LBS AT 130 PSI
	KG SINGLE						6630	6870	7110	7420		7660	7970	8120	8500	S 4250 KG AT 900 kPa
	KG DUAL						12480	12940	13380	13980		14420	15000	15280	16000	D 4000 KG AT 900 kPa
315/80R22.5 LR L 161/157 MG89, FG01	LBS SINGLE						15920	16500	17060	17820		18360	19120	19480	20400	S 10200 LBS AT 110 PSI
	LBS DUAL						28360	29400	30440	31760		32800	34080	34760	36360	D 9095 LBS AT 130 PSI
	KG SINGLE						7220	7480	7740	8080		8330	8670	8840	9250	S 4625 KG AT 900 kPa
	KG DUAL						12860	13340	13800	14400		14860	15460	15760	16500	D 4125 KG AT 900 kPa
385/55R22.5 LR L 164K-SINGLE ONLY R02 Pro Trailer	LBS SINGLE			14860	11570	16360	17200	17840	18460	19240		19860	20660	21260	22000	S 11000 LBS AT 130 PSI
	LBS DUAL															D
	KG SINGLE			6740	7130	7420	7800	8090	8370	8730		9010	9370	9640	1000	S 5000 KG AT 900 kPa
	KG DUAL															
385/65R22.5 LR L 164K-SINGLE ONLY G02 PRO, R02 Pro Trailer	LBS SINGLE				15720	16360	17200	17840	18460	19250		19860	20660	21260	22050	S 11025 LBS AT 130 PSI
	LBS DUAL															
	KG SINGLE				7130	7420	7800	8090	8370	8730		9010	9370	9640	1000	S 5000 KG AT 900 kPa
	KG DUAL															
425/65R22.5 LR L 165K-SINGLE ONLY G02 PRO	LBS SINGLE				17280	18000	18900	19580	20260	21160		21820	22800			S 11400 LBS AT 120 PSI
	LBS DUAL															
	KG SINGLE				7840	8160	8570	8880	9190	9600		9900	10300			S 5150 KG AT 830 kPa
	KG DUAL															

## WHEEL DIAMETER 24.5"

	PSI	70	75	80	85	90	95	100	105	110	112	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL
	kPa	480	520	550	590	620	*655/660	690	720	760	775	790	*825/830	860	900	
11R22.5 LR H 149/146 R89, R89 CS Drive, H89 Trailer, G02 on Off Multi axle, G02 On Off Drive	LBS SINGLE				11100	11680	12190	12700	13220	13280		13940	14320			S 7160 LBS AT 120 PSI
	LBS DUAL				21040	22040	22700	23360	24020	24820		25620	26440			D 6610 LBS AT 120 PSI
	KG SINGLE				5040	5300	5540	5780	6000	6160		6320	6500			S 3250 KG AT 830 kPa
	KG DUAL				9560	10000	10320	10640	10900	11280		11640	12000			D 3000 KG AT 830 kPa
285/75R24.5 LR H 147/144 R89, R89 CS Drive	LBS SINGLE				10420	10900	11350	11670	12080	12350		12880	13560			S 6780 LBS AT 125 PSI
	LBS DUAL				18960	19720	20820	21240	21980	22700		23440	24700			D 6175 LBS AT 120 PSI
	KG SINGLE				4720	4920	5150	5300	5480	5600		5840	6150			S 3075 KG AT 825 kPa
	KG DUAL				8600	8960	9440	9640	9960	10300		10640	11200			D 2800 KG AT 825 kPa

\* The First Number Reflects the Official Conversion and the Second Number Reflects the Previous Value. Some Products May Still Be Marked With The Previous Value.

\*\* 275/70R22.5 LR J can only be used on either 7.50" or 8.25" wheel. It cannot be used on 9" wheel.

\*\*\* 295/60R22.5 LR J can only be used on either 9.00" or 9.75" wheel. It cannot be used on 8.25 wheel.

## WHEEL DIAMETER 20" TUBELESS

	PSI	70	75	80	85	90	95	100	105	110	112	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL
	kPa	480	520	550	590	620	*655/660	690	720	760	775	790	*825/830	860	900	
335/80R20 MPT LR H 149 PS22-PISTA	LBS SINGLE	11120	11840	12400	13100	13620	14340									S 7170 LBS AT 95 PSI
	LBS DUAL															D
	KG SINGLE	5040	5370	5620	5940	6180	6500									S 3250 KG AT 660 kPa
	KG DUAL															D
365/80R20 MPT LR G 152 PS22_PISTA	LBS SINGLE	12780	13600	14220	15040	15660										S 7830 LBS AT 90 PSI
	LBS DUAL															D
	KG SINGLE	5790	6170	6450	6820	7100										S 3550 KG AT 620 kPa
	KG DUAL															D
1400R20 LR M 164/160 S02-PISTA	LBS SINGLE	15260	16280	17020	18020	18740	19680	20420	21120	22050						S 11025 LBS AT 110 PSI
	LBS DUAL	27480	29320	30640	32400	33720	35440	36720	38000	39680						D 9925 LBS AT 110 PSI
	KG SINGLE	6920	7380	7720	8170	8500	8930	9260	9580	10000						S 5000 KG AT 760 kPa
	KG DUAL	12460	13280	13900	14700	15280	16080	16660	17240	18000						D 4500 KG AT 760 kPa

## WHEEL DIAMETER 20" TUBELESS

	PSI	70	75	80	85	90	95	100	105	110	112	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL
	kPa	480	520	550	590	620	*655/660	690	720	760	775	790	*825/830	860	900	
365/85R20 LR J 164 PS22-PISTA	LBS SINGLE		15160	15860	16780	17460	18340	19020	19660	20540		21200	22050			S 11025 LBS AT 120 PSI
	LBS DUAL															D
	KG SINGLE		6880	7190	7610	7920	8320	8630	8920	9320		9610	10000			S 5000 KG AT 830 kPa
	KG DUAL															D
395/85R20 LR J 168 PS22-PISTA	LBS SINGLE			17260	18280	19000	19980	20700	21420	22380		23060	24000	24700		S 12350 LBS AT 125 PSI
	LBS DUAL															D
	KG SINGLE			7830	8290	8620	9060	9390	9720	10150		10460	10890	11200		S 5600 KG AT 860 kPa
	KG DUAL															D

## WHEEL DIAMETER 24" TUBE TYPE

	PSI	70	75	80	85	90	95	100	105	110	112	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL
	kPa	480	520	550	590	620	*655/660	690	720	760	775	790	*825/830	860	900	
1200R24TT 160/156 FG85, TG85, TQ:01	LBS SINGLE				14680	15280	16050	16650	17220	17970		18540	19290	19850		S 9925 LBS AT 125 PSI
	LBS DUAL				26100	27160	28550	29580	30600	31940		32960	34280	35280		D 8820 LBS AT 125 PSI
	KG SINGLE				6660	6930	7280	7550	7810	8150		8410	8750	9000		S 4500 KG AT 860 kPa
	KG DUAL				11840	12320	12940	13420	13880	14480		14940	15540	16000		D 4000 KG AT 860 kPa

\* The First Number Reflects the Official Conversion and the Second Number Reflects the Previous Value. Some Products May Still Be Marked With the Previous Value.