

H89 EVO

SATTTM
Spiral Advanced Technology for Truck



3SB

BWC


DLTC

FRC

HBW

RSR

NEW



The perfect balance between fuel efficiency and high mileage for long haul service



ENHANCED STEERING PRECISION AND EXCELLENT PERFORMANCE IN EVERY WEATHER CONDITION

Proprietary SATT Technology and improved compound formulation deliver superior handling and vehicle control at all times.

EVEN WEAR AND DURABILITY

A completely new decoupling groove design protects the footprint from lateral efforts to ensure even wear, and improved durability.

HIGH MILEAGE PERFORMANCE

New tread pattern with siped ribs and widened tread profile provide an optimized footprint, resulting in even wear and long tread life.

FUEL EFFICIENCY

The tread and base compounds deliver long tread life minimizing heat generation, ensuring excellent retreadability while complying with EPA SmartWay® requirements.

TIRE SIZE	PRODUCT NUMBER	INTERNATIONAL LOAD INDEX SPEED CODE	LOAD RANGE PLY RATING	WEIGHT LBS (Kg)	LOADED RADIUS in. (mm)	OVERALL DIAMETER in. (mm)	OVERALL WIDTH in. (mm)	APPROVED RIMS in.	MINIMUM DUAL SPACING in. (mm)	REVS PER MILE rpm (rpkm)	TREAD DEPTH 32nds (mm)	MAX SPEED mph (kph)	MAX TIRE LOAD		M+S	SMART WAY	
													SINGLE lbs. psi (kg kPa)	DUAL lbs. psi (kg kPa)			
295/75 R 22.5	6043907	149/146 L	H/16	126.1 (57.1)	18.8 (476)	40.2 (1020)	11.8 (300)	<u>9.00</u> 8.25	13.2 (335)	517 (321)	18/32 (14.0)	75 (120)	7160/123 (3250/850)	6610/123 (3000/850)	✓	PENDING	✓
11 R 22.5	6048107	146/143 L	H/16	129.0 (58.5)	19.1 (485)	41.2 (1047)	11.5 (292)	<u>8.25</u> 7.50	12.5 (318)	507 (315)	18/32 (14.0)	75 (120)	6610/120 (3000/825)	6005/120 (2725/825)	✓	✓	✓

Note: Rim underlined is measuring rim / Exceeding the lawful speed limit is neither recommended nor endorsed.