



Designed for steer axles providing high durability, comfort and mileage for regional operations.



TREAD A

TREAD B

LONG TIRE LIFE AND RETREADABILITY

The protected longitudinal grooves provide exceptional resistance to stone drilling for improved tire life and retreadability.

EVEN WEAR AND DURABILITY

The robust and wide longitudinal ribs together with the advanced tread compound provide outstanding resistance in high scrub operations and even wear.

TRACTION

The tread pattern depth delivers exceptional braking and traction performance throughout the whole life of the tire.

HIGH MILEAGE

The 4 zig-zag shape grooves minimize stress concentration at the base, enhancing wear uniformity and extending mileage..

FUEL EFFICIENCY

The innovative tread compound resists the demands of high-scrub operations while meeting EPA SmartWay® verified fuel efficiency standards in select sizes.

OE Manufacturer Partner: Navistar – IC Bus

TIRE SIZE	PRODUCT NUMBER	INTERNATIONAL LOAD INDEX SPEED CODE	LOAD RANGE PLY RATING	WEIGHT LBS (Kg)	LOADED RADIUS in. (mm)	OVERALL DIAMETER in. (mm)	OVERALL WIDTH in. (mm)	APPROVED RIMS in.	MINIMUM DUAL SPACING in. (mm)	REVS PER MILE rpm (rpk)	TREAD DEPTH 32nds (mm)	MAX SPEED mph (kph)	MAX TIRE LOAD		M+S	SMART WAY	
													SINGLE lbs. psi (kg kPa)	DUAL lbs. psi (kg kPa)			
275/70 R 22.5 (**)	3886307	148/145 M	J/18	119.3 (54.1)	17.5 (444)	37.6 (955)	11.1 (283)	8.25 (7.50)	11.9 (303)	552 (343)	17/32 (13.5)	81 (130)	6945/130 (3150/900)	6395/130 (2900/900)	✓	✓	✓
295/75 R 22.5	3462107	149/146 L	H/16	129.0 (58.5)	18.7 (476)	40.1 (1018)	11.9 (303)	9.00 (8.25)	13.2 (335)	518 (322)	21/32 (16.5)	75 (120)	7160/123 (3250/850)	6610/123 (3000/850)		✓	
315/80 R 22.5	6009607	158/156 M	L/20	142.9 (64.8)	19.8 (502)	42.5 (1080)	12.4 (314)	9.00 (9.75)	13.8 (351)	488 (304)	20/32 (16.0)	81 (130)	9370/130 (4250/900)	8820/130 (4000/900)	✓		
285/75 R 24.5	3830707	147/144 L	H/16	135.1 (61.3)	19.5 (496)	41.7 (1058)	11.1 (282)	8.25 (7.50, 8.25)	12.5 (318)	499 (310)	21/32 (17.0)	75 (120)	6780/120 (3075/830)	6175/120 (2800/830)			
11 R 22.5	3271707	146/143 L	H/16	132.5 (60.1)	19.2 (488)	41.5 (1054)	11.5 (293)	8.25 (7.50)	12.5 (318)	504 (313)	21/32 (16.5)	75 (120)	6610/120 (3000/830)	6005/120 (2750/830)		✓	
11 R 24.5 (**)	3462407	149/146 L	H/16	144.0 (65.3)	20.2 (513)	43.4 (1102)	11.2 (284)	8.25 (7.50)	12.5 (318)	482 (299)	20/32 (15.5)	75 (120)	7160/120 (3250/830)	6610/120 (3000/830)			

Note: Rim underlined is measuring rim / (**) Tire Size Available in Tread B / Important note: 275/70R22.5 LR J can only be used on either 7.50" or 8.25" wheel. It cannot be used on 9" wheel / Exceeding the lawful speed limit is neither recommended nor endorsed.