

R89 CS DRIVE

SATTTM
Spiral Advanced Technology for Truck



Regional closed shoulder drive optimized for extended tread life, retreadability and low rolling resistance.



LONG TIRE LIFE AND RETREADABILITY

The low rolling resistance tread compound, combined with the under-tread, extends tread life while reducing heat generation during operation, ensuring excellent retreadability.

PRECISION AND DRIVING COMFORT

The combination of optimized tread pattern geometry and specialized tread compound ensures even wear and a comfortable handling experience.

EXCELLENT GRIP AND TRACTION

The longitudinal and transversal groove geometry, along with casing dimensioning, ensures superior grip and traction during braking and acceleration throughout the tire's lifespan.

HIGH MILEAGE

The deep lug tread design ensures long-lasting mileage and maximum value throughout the tire's lifespan.

OE Manufacturer Partner: Navistar – IC Bus

TIRE SIZE	PRODUCT NUMBER	INTERNATIONAL LOAD INDEX SPEED CODE	LOAD RANGE PLY RATING	WEIGHT LBS (Kg)	LOADED RADIUS in. (mm)	OVERALL DIAMETER in. (mm)	OVERALL WIDTH in. (mm)	APPROVED RIMS in.	MINIMUM DUAL SPACING in. (mm)	REVS PER MILE rpm (rpk)	TREAD DEPTH 32nds (mm)	MAX SPEED mph (kph)	MAX TIRE LOAD		M+S	SMART WAY	
													SINGLE lbs. psi (kg kPa)	DUAL lbs. psi (kg kPa)			
295/75 R 22.5	3797100	149/146 L	H/16	140.7 (63.8)	19.0 (481)	40.6 (1032)	12.0 (304)	<u>9.00</u> 8.25	13.2 (335)	511 (318)	30/32 (23.5)	75 (120)	7160/123 (3250/850)	6610/123 (3000/850)	✓		
285/75 R 24.5	3830800	147/144 L	H/16	145.7 (66.1)	19.7 (501)	42.0 (1068)	11.1 (282)	<u>8.25</u> 7.50	12.5 (318)	494 (307)	30/32 (23.5)	75 (120)	6780/120 (3075/830)	6175/120 (2800/830)	✓		
11 R 22.5	379700	146/143 L	H/16	142.6 (64.7)	19.5 (494)	42.0 (1068)	11.6 (295)	<u>8.25</u> 7.50	12.5 (318)	497 (309)	30/32 (23.5)	75 (120)	6610/120 (3000/830)	6005/120 (2725/830)	✓		
11 R 24.5	3462500	149/146 L	H/16	153.7 (69.7)	20.4 (519)	44.0 (1117)	11.2 (284)	<u>8.25</u> 7.50	12.5 (318)	475 (295)	29/32 (23.0)	75 (120)	7160/120 (3250/830)	6610/120 (3000/830)	✓		

Note: Rim underlined is measuring rim / Exceeding the lawful speed limit is neither recommended nor endorsed.