

FG85™



All position tire, dedicated to mixed use vehicles, engineered to resist to severe service, enhancing integrity, resistance to laceration and retreadability.



RESISTANCE TO LACERATIONS

The robust circumferential ribs, rounded contour, and tread groove design provide maximum resistance to lacerations and stone retention.

TRACTION AND GRIP

The zig-zag longitudinal grooves and wide transversal shoulder grooves improve traction and grip on all surfaces, ensuring optimal road handling.

TIRE DURABILITY

The specially formulated tread compound, designed to maintain lower operating temperatures, ensures tire durability and enhances retreadability.

HIGH MILEAGE

The tread depth and under-tread design minimize the risk of casing damage, ensuring extended tire life and maximum mileage.

TIRE SIZE	PRODUCT NUMBER	INTERNATIONAL LOAD INDEX SPEED CODE	LOAD RANGE PLY RATING	WEIGHT LBS (Kg)	LOADED RADIUS in. (mm)	OVERALL DIAMETER in. (mm)	OVERALL WIDTH in. (mm)	APPROVED RIMS in.	MINIMUM DUAL SPACING in. (mm)	REVS PER MILE rpm (rpkm)	TREAD DEPTH 32nds (mm)	MAX SPEED mph (kph)	MAX TIRE LOAD		M+S	SMART WAY	
													SINGLE lbs. psi (kg kPa)	DUAL lbs. psi (kg kPa)			
12.00 R 24 TT	3780307	160/156 K	L/20	170.6 (77.4)	22.2 (563)	48.2 (1224)	11.8 (300)	<u>8.25</u> 7.50, 8.0, 9.0	14.2 (360)	434 (270)	21/32 (17.0)	68 (110)	9925/125 (4500/860)	8820/125 (4000/860)	✓		✓

Note: Rim underlined is measuring rim / Exceeding the lawful speed limit is neither recommended nor endorsed