

FR:01™

SATT™
Spiral Advanced Technology for Truck



Tire designed for fitment of steer axle ensuring cost efficiency, comfort and safety.



MAXIMUM SAFETY

The tread design with 4 zig-zag shape grooves and robust longitudinal ribs reduce braking distance and enhance driving safety.

HIGH MILEAGE AND EVEN WEAR

The shoulder tread contour (patented) ensures proper distribution of footprint contact pressure, promoting even wear and high mileage.

STONE TRAPPING PREVENTION

The optimized central grooves geometry enhances stone ejection.

RESISTANCE TO LATERAL IMPACTS

The sidewall protection ribs increase resistance to lateral impacts and abrasion.

MAXIMUM STEERING PRECISION

Specially engineered grooves and siping geometry ensures steering precision and excellent dry and wet handling.

OE Manufacturer Partner: Navistar – International

TIRE SIZE	PRODUCT NUMBER	INTERNATIONAL LOAD INDEX SPEED CODE	LOAD RANGE PLY RATING	WEIGHT LBS (Kg)	LOADED RADIUS in. (mm)	OVERALL DIAMETER in. (mm)	OVERALL WIDTH in. (mm)	APPROVED RIMS in.	MINIMUM DUAL SPACING in. (mm)	REVS PER MILE rpm (rpkm)	TREAD DEPTH 32nds (mm)	MAX SPEED mph (kph)	MAX TIRE LOAD				M+S	SMART WAY	
													SINGLE lbs. psi (kg kPa)	DUAL lbs. psi (kg kPa)					
295/80 R 22.5	2343907	152/148 M	J/18	140.2 (63.6)	19.4 (492)	41.6 (1057)	11.7 (297)	<u>9.00</u> 8.25	13.2 (335)	499 (310)	20/32 (16.0)	81 (130)	7830/125 (3550/860)	6945/125 (3150/860)					
12 R 22.5	3249807	152/148 M	J/18	141.5 (64.2)	19.7 (501)	42.7 (1085)	11.9 (302)	<u>9.00</u> 8.25	13.3 (338)	489 (304)	20/32 (16.0)	81 (130)	7830/125 (3550/860)	6945/125 (3150/860)					

Note: Rim underlined is measuring rim / Exceeding the lawful speed limit is neither recommended nor endorsed.