

# TR:01™

**SATT**™  
Spiral Advanced Technology for Truck



Tire designed for fitment on drive axle ensuring cost efficiency, comfort and safety.



**DIRECTIONAL TREAD**



## TRACTION & ACOUSTIC COMFORT

The directional tread pattern and optimized tread block pitch sequence enhance traction and reduce noise for maximum acoustic comfort.

## LONG TREAD LIFE

The tread width and groove depth improve durability enhancing robustness and mileage.

## HIGH RESISTANCE

The sidewall protection ribs enhance resistance to lateral impacts and abrasion.

## STONES TRAPPING PREVENTION

Optimized lateral grooves geometry and depth promote even wear and facilitate effective stone ejection.

OE Manufacturer Partner: Navistar – International

| TIRE SIZE      | PRODUCT NUMBER | INTERNATIONAL LOAD INDEX SPEED CODE | LOAD RANGE PLY RATING | WEIGHT LBS (Kg) | LOADED RADIUS in. (mm) | OVERALL DIAMETER in. (mm) | OVERALL WIDTH in. (mm) | APPROVED RIMS in. | MINIMUM DUAL SPACING in. (mm) | REVS PER MILE rpm (rpkm) | TREAD DEPTH 32nds (mm) | MAX SPEED mph (kph) | MAX TIRE LOAD            |                        | M+S | SMART WAY |  |
|----------------|----------------|-------------------------------------|-----------------------|-----------------|------------------------|---------------------------|------------------------|-------------------|-------------------------------|--------------------------|------------------------|---------------------|--------------------------|------------------------|-----|-----------|--|
|                |                |                                     |                       |                 |                        |                           |                        |                   |                               |                          |                        |                     | SINGLE lbs. psi (kg kPa) | DUAL lbs. psi (kg kPa) |     |           |  |
| 295/80 R 22.5* | 2344000        | 152/148 M                           | J/18                  | 154.5 (70.1)    | 19.6 (498)             | 42.1 (1070)               | 11.7 (297)             | <u>9.00</u> 8.25  | 13.2 (335)                    | 493 (306)                | 28/32 (22.5)           | 81 (130)            | 7830/125 (3550/860)      | 6945/125 (3150/860)    | ✓   |           |  |
| 12 R 22.5*     | 3249900        | 152/148 M                           | J/18                  | 151.0 (68.5)    | 19.9 (505)             | 43.1 (1094)               | 11.9 (302)             | <u>9.00</u> 8.25  | 13.3 (338)                    | 485 (302)                | 26/32 (20.5)           | 81 (130)            | 7830/125 (3550/860)      | 6945/125 (3150/860)    | ✓   |           |  |

Note: Rim underlined is measuring rim / \* Directional tread pattern / Exceeding the lawful speed limit is neither recommended nor endorsed.