

TG:01™

SATT™
Spiral Advanced Technology for Truck



BWC

HBW

NEW



Designed for fitment on drive axle of vehicles used in construction sites, and delivers resistance to laceration, high traction on rough terrains and mud, and mileage on asphalt roads.



DIRECTIONAL TREAD



MILEAGE

The large tread width ensures high mileage performance.

TRACTION AND EVEN WEAR

The optimized groove design improves traction and even wear, and ensures easy self-cleaning.

RESISTANCE

The patented protective elements at the bottom of the grooves prevent stone trapping, enhancing maximum tire durability and resistance.

ACOUSTIC COMFORT

The directional tread pattern enhances traction, reduces noise, and promotes even wear.

TIRE SIZE	PRODUCT NUMBER	INTERNATIONAL LOAD INDEX SPEED CODE	LOAD RANGE PLY RATING	WEIGHT LBS (Kg)	LOADED RADIUS in. (mm)	OVERALL DIAMETER in. (mm)	OVERALL WIDTH in. (mm)	APPROVED RIMS in.	MINIMUM DUAL SPACING in. (mm)	REVS PER MILE rpm (rpk)	TREAD DEPTH 32nds (mm)	MAX SPEED mph (kph)	MAX TIRE LOAD		M+S	SMART WAY	
													SINGLE lbs. psi (kg kPa)	DUAL lbs. psi (kg kPa)			
315/80 R 22.5*	3558500	156/150 K	J/18	165.6 (75.1)	20.0 (507)	43.0 (1093)	12.4 (314)	<u>9.00</u> 9.75	13.8 (351)	483 (300)	28/32 (22.5)	68 (110)	8820/125 (4000/860)	7390/125 (3350/860)	√		√

Note: Rim underlined is measuring rim / * Directional Tread Pattern / Exceeding the lawful speed limit is neither recommended nor endorsed.