

FG:01™

SATT™
Spiral Advanced Technology for Truck



Designed for steer - all position on vehicles used in severe service operation, features chip & cut resistant compound and grip in on-off road application.



MILEAGE

The lateral and central grooves, featuring a built-in step, ensure high mileage.

STONE TRAPPING PREVENTION

The grooves with built-in stepstone ejectors prevent stone trapping, enhancing resistance to lacerations.

HIGH DURABILITY

Sidewall protection ribs provide strong resistance to lateral impacts and abrasion.

TIRE SIZE	PRODUCT NUMBER	INTERNATIONAL LOAD INDEX SPEED CODE	LOAD RANGE PLY RATING	WEIGHT LBS (Kg)	LOADED RADIUS in. (mm)	OVERALL DIAMETER in. (mm)	OVERALL WIDTH in. (mm)	APPROVED RIMS in.	MINIMUM DUAL SPACING in. (mm)	REVS PER MILE rpm (rpk)	TREAD DEPTH 32nds (mm)	MAX SPEED mph (kph)	MAX TIRE LOAD		M+S	SMART WAY	
													SINGLE lbs. psi (kg kPa)	DUAL lbs. psi (kg kPa)			
315/80 R 22.5	3886207	161/157 K	L/20	147.0 (66.7)	19.8 (502)	42.5 (1080)	12.4 (314)	<u>9.00</u> 9.75	13.8 (351)	488 (304)	23/32 (18.0)	68 (110)	10200/130 (4625/900)	9095/130 (4125/900)	√		√

Note: Rim underlined is measuring rim / Exceeding the lawful speed limit is neither recommended nor endorsed.