


H89 TRAILER

SATTTM
Spiral Advanced Technology for Truck



Engineered for fuel efficiency, extended mileage, and superior road holding for long haul transports.



CASING DURABILITY

The 3SB SATT Construction in tread crown area, the tread pattern design with stone ejectors in every groove and the advanced compound formulation in the bead area optimize heat dispersion, ensuring maximum casing durability and retreadability.

FUEL EFFICIENCY

The tread compound is engineered to maximize fuel efficiency while meeting EPA SmartWay[®] verified Rolling Resistance standards.

LONG TIRE LIFE

The optimized tire profile, the shoulder protection through support groove and the innovative tread compound formulation ensure extended tire longevity.

STABLE HANDLING ON EVERY ROAD CONDITION

The tread pattern, featuring a zig-zag groove design, M+S tread compound and 4 wide longitudinal grooves, provide exceptional traction and stability.

TIRE SIZE	PRODUCT NUMBER	INTERNATIONAL LOAD INDEX SPEED CODE	LOAD RANGE PLY RATING	WEIGHT LBS (Kg)	LOADED RADIUS in. (mm)	OVERALL DIAMETER in. (mm)	OVERALL WIDTH in. (mm)	APPROVED RIMS in.	MINIMUM DUAL SPACING in. (mm)	REVS PER MILE rpm (rpkm)	TREAD DEPTH 32nds (mm)	MAX SPEED mph (kph)	MAX TIRE LOAD		M+S	SMART WAY	
													SINGLE lbs. psi (kg kPa)	DUAL lbs. psi (kg kPa)			
295/75 R 22.5	3263700	144/141 M	G/14	112.7 (51.1)	18.5 (470)	39.5 (1004)	11.9 (302)	<u>9.00</u> 8.25	13.2 (335)	525 (327)	12/32 (9.5)	81 (130)	6175/110 (2800/760)	5675/110 (2575/760)		✓	

Note: Rim underlined is measuring rim / Exceeding the lawful speed limit is neither recommended nor endorsed.