

FH:01™ ENERGY™

SATT™
Spiral Advanced Technology for Truck



The optimal combination between fuel efficiency, high mileage and steering precision.



STEERING PRECISION

Innovative groove geometry (wave shape) enhance progressive response and maximum steering precision.

DURABILITY AND RETREADABILITY

Stone trapping is prevented thanks to groove profile design allowing excellent casing retreadability.

EVEN WEAR AND HIGH MILEAGE

The RSR - Rotated Shoulder Rib - enhances the correct distribution of the footprint contact pressure for optimal even wear and high mileage.

LOW ROLLING RESISTANCE

The innovative compound formulation enriched in silica and nano filler ensures low heat generation for low rolling resistance, long tire life and retreadability.

TIRE SIZE	PRODUCT NUMBER	INTERNATIONAL LOAD INDEX SPEED CODE	LOAD RANGE PLY RATING	WEIGHT LBS (Kg)	LOADED RADIUS in. (mm)	OVERALL DIAMETER in. (mm)	OVERALL WIDTH in. (mm)	APPROVED RIMS in.	MINIMUM DUAL SPACING in. (mm)	REVS PER MILE rpm (rpk)	TREAD DEPTH 32nds (mm)	MAX SPEED mph (kph)	MAX TIRE LOAD		M+S	SMART WAY	
													SINGLE lbs. psi (kg kPa)	DUAL lbs. psi (kg kPa)			
295/60 R 22.5	6077907	150/147 L	J/18	108.0 (49.0)	17.0 (431)	36.1 (918)	11.7 (298)	<u>9.00</u> 9.75	13.0 (329)	578 (360)	13/32 (10.5)	75 (120)	7390/130 (3350/900)	6780/130 (3075/900)	✓		✓

Note: Rim underlined is measuring rim / Exceeding the lawful speed limit is neither recommended nor endorsed / 295/60R22.5 LR J can only be used on either 9.00" or 9.75" wheel. It cannot be used on 8.25 wheel.