

R02 PROFUEL STEER



The latest generation of steer tires for regional transport designed for maximum versatility, efficiency and high durability standards.



INNOVATIVE TREAD PATTERN

The 4 zig-zag shape grooves and robust longitudinal ribs reduce braking distance, improve road holding and driving safety.

STONES TRAPPING PREVENTION

Stone ejectors at the base of every groove prevent stone trapping ensuring great durability and retreadability.

HIGH MILEAGE PERFORMANCE AND EVEN WEAR

The new shoulder tread contour ensures uniform footprint contact pressure, as well as low noise emission for maximum comfort.

ENHANCED TRACTION

The functional sipes provide superior traction in all weather conditions.

OE Manufacturer Partner: Navistar – International

TIRE SIZE	PRODUCT NUMBER	INTERNATIONAL LOAD INDEX SPEED CODE	LOAD RANGE PLY RATING	WEIGHT LBS (Kg)	LOADED RADIUS in. (mm)	OVERALL DIAMETER in. (mm)	OVERALL WIDTH in. (mm)	APPROVED RIMS in.	MINIMUM DUAL SPACING in. (mm)	REVS PER MILE rpm (rpkm)	TREAD DEPTH 32nds (mm)	MAX SPEED mph (kph)	MAX TIRE LOAD		M+S	SMART WAY	
													SINGLE lbs. psi (kg kPa)	DUAL lbs. psi (kg kPa)			
205/75 R 17.5	4133907	124/122 M	G/14	51.6 (23.4)	13.9 (354)	29.7 (754)	8.3 (211)	6.00 5.25, 6.75	9.1 (231)	700 (435)	13/32 (10.0)	81 (130)	3525/110 (1600/760)	3305/110 (1500/760)	✓		✓
215/75 R 17.5	4132907	128/126 M	G/14	57.8 (26.2)	14.2 (361)	30.4 (772)	8.5 (216)	6.00 6.75	9.4 (239)	683 (425)	13/32 (10.5)	81 (130)	3970/110 (1800/760)	3750/110 (1700/760)	✓		✓
235/75 R 17.5	4133107	132/130 M	G/14	67.5 (30.6)	14.7 (374)	31.6 (802)	9.4 (238)	6.75 7.50	10.3 (262)	658 (409)	14/32 (11.5)	81 (130)	4410/112 (2000/775)	4190/112 (1900/775)	✓		✓
225/70 R 19.5	6008407	128/126 N	G/14	69.7 (31.6)	15.0 (380)	32.1 (816)	9.1 (231)	6.75 6.00	10.0 (254)	646 (402)	16/32 (12.5)	87 (140)	3970/110 (1800/760)	3750/110 (1700/760)	✓		✓
245/70 R 19.5	4133507	136/134 M	H/16	75.0 (34.0)	15.4 (390)	33.1 (841)	10.0 (254)	7.50 6.75	11.0 (279)	627 (390)	14/32 (11.5)	81 (130)	4940/120 (2240/825)	4675/120 (2120/825)	✓		✓
265/70 R 19.5	4133707	140/138 M	G/14	81.6 (37.0)	15.7 (399)	34.0 (863)	10.6 (268)	7.50 6.75, 8.25	11.3 (286)	611 (380)	15/32 (12.0)	81 (130)	5510/112 (2500/775)	5205/112 (2360/775)	✓		✓
285/70 R 19.5	4090507	146/144 L	H/16	95.9 (43.5)	16.2 (411)	35.1 (891)	11.4 (289)	8.25 7.50, 9.00	12.5 (318)	592 (368)	16/32 (13.0)	75 (120)	6615/125 (3000/860)	6175/125 (2800/860)	✓		✓

Note: Rim underlined is measuring rim / Exceeding the lawful speed limit is neither recommended nor endorsed.