

R02 PROFUEL DRIVE



The latest generation of drive tires for regional transport designed for maximum versatility, efficiency and high durability standards.



ENHANCED MILEAGE

The new tread geometry featuring an innovative tread block step sequence, ensures uniform wear and maximum safety.

EVEN WEAR

The innovative bumper technology reduces vibrations enhancing regular wear, acoustic comfort and stone trapping prevention.

LOW ROLLING RESISTANCE

The advanced compound ensures low rolling resistance, superior grip and long-lasting durability.

FUNCTIONAL DESIGN

The optimized sipes and transversal grooves design provide superior traction in all weather conditions.

OE Manufacturer Partner: Navistar – International

TIRE SIZE	PRODUCT NUMBER	INTERNATIONAL LOAD INDEX SPEED CODE	LOAD RANGE PLY RATING	WEIGHT LBS (Kg)	LOADED RADIUS in. (mm)	OVERALL DIAMETER in. (mm)	OVERALL WIDTH in. (mm)	APPROVED RIMS in.	MINIMUM DUAL SPACING in. (mm)	REVS PER MILE rpm (rpkm)	TREAD DEPTH 32nds (mm)	MAX SPEED mph (kph)	MAX TIRE LOAD		M+S	SMART WAY	
													SINGLE lbs. psi (kg kPa)	DUAL lbs. psi (kg kPa)			
225/70 R 19.5	6008500	128/126 N	G/14	72.1 (32.7)	15.0 (382)	32.3 (820)	9.3 (235)	<u>6.75</u> 6.00	10.0 (254)	643 (400)	18/32 (14.5)	87 (140)	3970/110 (1800/760)	3750/110 (1700/760)	✓		✓
245/70 R 19.5	4133600	136/134 M	H/16	75.8 (34.4)	15.4 (391)	33.1 (842)	10.0 (254)	<u>7.50</u> 6.75	11.0 (279)	627 (389)	15/32 (12.0)	81 (130)	4940/120 (2240/825)	4675/120 (2120/825)	✓		✓
265/75 R 19.5	4133800	140/138 M	G/14	86.2 (39.1)	15.8 (401)	34.2 (868)	10.6 (268)	<u>7.50</u> 6.75, 8.25	11.3 (286)	608 (378)	18/32 (14.5)	81 (130)	5510/112 (2500/775)	5205/112 (2360/775)	✓		✓
285/70 R 19.5	4090600	146/144 L	H/16	100.3 (45.5)	16.2 (413)	35.2 (895)	11.4 (289)	<u>8.25</u> 7.50, 9.00	12.5 (318)	589 (366)	19/32 (15.0)	75 (120)	6615/125 (3000/860)	6175/125 (2800/860)	✓		✓

Note: Rim underlined is measuring rim / Exceeding the lawful speed limit is neither recommended nor endorsed.