

G02 PRO



The latest generation of all position tires for mixed use service featuring low operational costs, extended tire life and great durability.



DURABILITY AND RETREADABILITY

The stone ejectors at the bottom of the grooves promote stone trapping prevention for tire durability and retreadability.

MILEAGE

The optimized tread pattern design with wider tread and deeper grooves grant high land to sea ratio for great performance in wet and dry conditions and high mileage.

EVEN WEAR

The shallow pockets and robust shoulders enhance even wear.

EVEN WEAR AND TRACTION

The innovative Bumper Technology (Prometeon patent) promotes the reduction of tread movement and vibrations enhancing regular wear, traction and safety in any conditions.

LOAD CAPACITY

The new reinforced casing construction increases load capacity up to 10 tonnes per axle.

TIRE SIZE	PRODUCT NUMBER	INTERNATIONAL LOAD INDEX SPEED CODE	LOAD RANGE PLY RATING	WEIGHT LBS (Kg)	LOADED RADIUS in. (mm)	OVERALL DIAMETER in. (mm)	OVERALL WIDTH in. (mm)	APPROVED RIMS in.	MINIMUM DUAL SPACING in. (mm)	REVS PER MILE rpm (rpk)	TREAD DEPTH 32nds (mm)	MAX SPEED mph (kph)	MAX TIRE LOAD		M+S	SMART WAY	
													SINGLE lbs. psi (kg kPa)	DUAL lbs. psi (kg kPa)			
385/65 R 22.5	4028807	164 K	L/20	166.0 (75.3)	19.8 (503)	42.9 (1089)	15.1 (383)	<u>11.75</u> 12.25		488 (303)	21/32 (16.5)	68 (110)	11025/130 (5000/900)		✓		✓
425/65 R 22.5	6044807	165 K	L/20	199.5 (90.2)	20.4 (519)	44.3 (1126)	16.5 (420)	<u>12.25</u> 13.00, 14.00		472 (293)	23/32 (18.0)	68 (110)	11400/120 (5150/825)		✓		✓

Note: Rim underlined is measuring rim / Exceeding the lawful speed limit is neither recommended nor endorsed.