

R02 PRO TRAILER 17.5" & 19.5"

NEW



The latest generation of trailer tires for regional and long-haul transport designed for maximum versatility, durability and mileage.



LONG TIRE LIFE

The innovative tread compound grants mileage, integrity and long tire life.

OPTIMIZED WATER DRAINAGE

The optimized tread pattern design with wide tread and deep grooves enhances water drainage and reduced braking distance in wet conditions.

ROBUSTNESS

The robust shoulder promotes tear resistance to chipping and chunking and resistance to lateral sliding.

TIRE SIZE	PRODUCT NUMBER	INTERNATIONAL LOAD INDEX SPEED CODE	LOAD RANGE PLY RATING	WEIGHT LBS (Kg)	LOADED RADIUS in. (mm)	OVERALL DIAMETER in. (mm)	OVERALL WIDTH in. (mm)	APPROVED RIMS in.	MINIMUM DUAL SPACING in. (mm)	REVS PER MILE rpm (rpk)	TREAD DEPTH 32nds (mm)	MAX SPEED mph (kph)	MAX TIRE LOAD		M+S	SMART WAY	
													SINGLE lbs. psi (kg kPa)	DUAL lbs. psi (kg kPa)			
205/65 R 17.5	6020300	132/130 J	J/18	58.2 (26.0)	12.9 (329)	28.0 (711)	8.1 (205)	<u>6.00</u> 6.75	9.1 (231)	747 (464)	14/32 (11.0)	62 (100)	4410/130 (2000/900)	4190/130 (1900/900)	✓		✓
215/75 R 17.5	6020400	136/134 K	J/18	67.2 (30.5)	14.0 (354)	30.5 (775)	8.5 (215)	<u>6.00</u> 6.75	9.4 (239)	681 (423)	15/32 (12.0)	68 (110)	4940/130 (2240/900)	4675/130 (2120/900)	✓		✓
235/75 R 17.5	6018100	143/141 K	J/18	79.8 (36.2)	14.3 (363)	31.3 (796)	9.5 (241)	<u>6.75</u> 7.50	10.3 (262)	663 (412)	15/32 (12.0)	68 (110)	6005/130 (2725/900)	5675/130 (2725/900)	✓		✓
245/70 R 17.5	6018200	143/141 L	J/18	79.8 (36.2)	14.3 (363)	31.3 (796)	10.0 (253)	<u>7.50</u> 6.75	11.0 (279)	663 (412)	15/32 (12.0)	75 (120)	6005/130 (2725/900)	5675/130 (2575/900)	✓		✓
285/70 R 19.5	6020700	150/148 K	J/18	100.5 (45.6)	16.0 (406)	35.1 (891)	11.3 (286)	<u>8.25</u> 9.00	12.5 (318)	592 (368)	18/32 (14.5)	68 (110)	7390/130 (3350/900)	6940/130 (3150/900)	✓		✓

Note: Rim underlined is measuring rim / Exceeding the lawful speed limit is neither recommended nor endorsed.