

MG89

SATTTM
Spiral Advanced Technology for Truck



Robust high load carrying capacity all-position tire designed for high scrub refuse and sanitation operations



RESISTANCE TO LATERAL IMPACTS

Robust sidewall thickness ensure protection from curb / hazard impacts.

RESISTANCE TO LACERATION AND ABRASION

Tread pattern design and high scrub tread compound together with groove profile ensure optimal performance in the most demanding service conditions.

CASING DURABILITY AND INTEGRITY

Heavy duty casing design (both in crown area as well as bead area) delivers superior resistance to landfill hazards and start/stop service pattern, ensuring exceptional retreadability.

HIGH MILEAGE IN DEMANDING SERVICE CONDITIONS

High scrub tread compound deliver consistent performance in refuse / sanitation operations.

TIRE SIZE	PRODUCT NUMBER	INTERNATIONAL LOAD INDEX SPEED CODE	LOAD RANGE PLY RATING	WEIGHT LBS (Kg)	LOADED RADIUS in. (mm)	OVERALL DIAMETER in. (mm)	OVERALL WIDTH in. (mm)	APPROVED RIMS in.	MINIMUM DUAL SPACING in. (mm)	REVS PER MILE rpm (rpkm)	TREAD DEPTH 32nds (mm)	MAX SPEED mph (kph)	MAX TIRE LOAD		M+S	SMART WAY	
													SINGLE lbs. psi (kg kPa)	DUAL lbs. psi (kg kPa)			
315/80 R 22.5	3840107	161/157 K	L/20	158.3 (71.8)	19.9 (506)	42.9 (1089)	12.4 (316)	<u>9.00</u> 9.75	13.8 (351)	484 (301)	25/32 (19.5)	68 (100)	10200/130 (4625/900)	9095/130 (4625/900)	✓		✓

Note: Rim underlined is measuring rim / Exceeding the lawful speed limit is neither recommended nor endorsed.