

R89 DRIVE

SATTTM
Spiral Advanced Technology for Truck



Regional open shoulder drive tire optimized for high traction, long tread life and great retreadability.



DIRECTIONAL TREAD



LONG TIRE LIFE AND RETREADABILITY

The low rolling resistance tread compound, combined with the under-tread, extends tread life while reducing heat generation during operation, ensuring excellent retreadability.

EXCELLENT GRIP AND TRACTION

The longitudinal and transversal groove geometry, along with casing dimensioning, ensures superior grip and traction during braking and acceleration throughout the tire's lifespan.

HIGH DURABILITY

The advanced tread pattern design protects the tread blocks, greatly reducing lug base damage and tearing while enhancing retreadability.

HIGH MILEAGE

The deep lug tread design ensures long-lasting mileage and maximum value throughout the tire's lifespan.

TIRE SIZE	PRODUCT NUMBER	INTERNATIONAL LOAD INDEX SPEED CODE	LOAD RANGE PLY RATING	WEIGHT LBS (Kg)	LOADED RADIUS in. (mm)	OVERALL DIAMETER in. (mm)	OVERALL WIDTH in. (mm)	APPROVED RIMS in.	MINIMUM DUAL SPACING in. (mm)	REVS PER MILE rpm (rpk)	TREAD DEPTH 32nds (mm)	MAX SPEED mph (kph)	MAX TIRE LOAD		M+S	SMART WAY	
													SINGLE lbs. psi (kg kPa)	DUAL lbs. psi (kg kPa)			
295/75 R 22.5*	3462300	149/146 L	H/16	141.1 (64.0)	19.0 (482)	40.7 (1033)	11.9 (303)	<u>9.00</u> 8.25	13.2 (335)	511 (317)	30/32 (24.0)	75 (120)	7160/123 (3250/850)	6610/123 (3000/850)	✓		
315/80 R 22.5*	3886100	158/156 M	L/20	158.3 (71.8)	20.0 (507)	43.0 (1093)	12.4 (314)	<u>9.00</u> 9.75	13.8 (351)	483 (300)	28/32 (22.0)	81 (130)	9370/130 (4250/900)	8820/130 (4000/900)	✓		✓
11 R 22.5*	3271800	146/143 L	H/16	141.1 (64.0)	19.4 (494)	4205 (1067)	11.5 (293)	<u>8.25</u> 7.50	12.5 (318)	498 (309)	30/32 (23.5)	75 (120)	6610/120 (3000/830)	6005/120 (2725/830)	✓		

Note: Rim underlined is measuring rim / * Directional tread pattern / Exceeding the lawful speed limit is neither recommended nor endorsed