

G02 ON-OFF MULTIAXLE



The latest generation all position tire designed for severe service, featuring high retreadability and chip & cut resistant compound for outstanding on-off road performance.



TEARING RESISTANCE

The reinforced and connected tread blocks grant maximum tearing resistance.

CARCASS DURABILITY

The built-in stone ejectors in all the grooves promote stone trapping prevention for the maximum carcass durability.

HANDLING AND DURABILITY

The closed shoulders ensure great handling and tire durability for the whole tire life.

STRONG BRAKING PERFORMANCE

The special shape sipes reduces braking distance.

TIRE SIZE	PRODUCT NUMBER	INTERNATIONAL LOAD INDEX SPEED CODE	LOAD RANGE PLY RATING	WEIGHT LBS (Kg)	LOADED RADIUS in. (mm)	OVERALL DIAMETER in. (mm)	OVERALL WIDTH in. (mm)	APPROVED RIMS in.	MINIMUM DUAL SPACING in. (mm)	REVS PER MILE rpm (rpkm)	TREAD DEPTH 32nds (mm)	MAX SPEED mph (kph)	MAX TIRE LOAD		M+S	SMART WAY	
													SINGLE lbs. psi (kg kPa)	DUAL lbs. psi (kg kPa)			
11 R 22.5	6007807	146/143 K	H/16	133.4 (60.5)	19.3 (491)	41.7 (1060)	11.5 (293)	<u>8.25</u> 7.50	12.5 (318)	501 (311)	24/32 (19.0)	68 (110)	6610/120 (3000/825)	6005/120 (2725/825)	✓		✓
11 R 24.5	6008007	149/146 K	H/16	141.5 (64.2)	20.3 (516)	43.7 (1110)	11.2 (284)	<u>8.25</u> 7.50	12.5 (318)	478 (297)	24/32 (19.0)	68 (110)	7160/120 (3250/825)	6610/120 (3000/825)	✓		✓
12 R 22.5	6003207	152/149 K	J/18	147.5 (66.9)	19.9 (504)	43.0 (1092)	12.0 (306)	<u>9.00</u> 8.25	13.5 (343)	486 (302)	25/32 (19.5)	68 (110)	7830/123 (3550/850)	7160/123 (3250/850)	✓		✓

Note: Rim underlined is measuring rim / Exceeding the lawful speed limit is neither recommended nor endorsed.