

R02 PROWAY DRIVE

SATTTM
 Spiral Advanced Technology for Truck


3SB


BWC

DLTC

FRC

HBW

RSR

NEW


Product line dedicated to versatility application with excellent Total Cost of Ownership (TCO), high mileage and durability to deliver the most efficient driving performance



TREAD A

TREAD B

**DIRECTIONAL TREAD
[TREAD A ONLY]**

TRACTION & ACOUSTIC COMFORT

Directional tread pattern and optimized tread block pitch sequence offer better traction and acoustic comfort.


LONG TREAD LIFE

Tread width and groove depth enhance robustness and mileage


INNOVATIVE TREAD PATTERN

Optimized design reduces noise generation, minor tread block movement and energy dissipation.

TIRE SIZE	PRODUCT NUMBER	INTERNATIONAL LOAD INDEX SPEED CODE	LOAD RANGE PLY RATING	WEIGHT LBS (Kg)	LOADED RADIUS in. (mm)	OVERALL DIAMETER in. (mm)	OVERALL WIDTH in. (mm)	APPROVED RIMS in.	MINIMUM DUAL SPACING in. (mm)	REVS PER MILE rpm (rpkm)	TREAD DEPTH 32nds (mm)	MAX SPEED mph (kph)	MAX TIRE LOAD		M+S	SMART WAY	
													SINGLE lbs. psi (kg kPa)	DUAL lbs. psi (kg kPa)			
295/60 R 22.5*	6026200	150/147 L	J/18	122.8 (55.7)	17.2 (437)	36.7 (931)	11.8 (299)	<u>9.00</u> 9.75	13.0 (329)	570 (354)	21/32 (17,0)	75 (120)	7390/130 (3350/900)	6780/130 (3075/900)	✓		✓
295/80 R 22.5 (**)	6002700	152/148 M	J/18	157.6 (71.5)	19.6 (497)	42.1 (1069)	12.0 (304)	<u>9.00</u> 8.25	13.2 (335)	493 (307)	28/32 (22.5)	81 (130)	7830/123 (3550/850)	6940/123 (3150/850)	✓		✓

Note: Rim underlined is measuring rim / (**) Tire Size Available in Tread B / * Directional Tread Pattern / Exceeding the lawful speed limit is neither recommended nor endorsed. / 295/60R22.5 LR J can only be used on either 9.00" or 9.75" wheel. It cannot be used on 8.25 wheel.