

R02 PROWAY STEER

NEW

SATT™
Spiral Advanced Technology for Truck

Product line dedicated to versatility application with excellent Total Cost of Ownership (TCO), high mileage and durability to deliver the most efficient driving performance.



INNOVATIVE TREAD PATTERN

4 zig-zag shape grooves and robust longitudinal ribs are designed to reduce braking distance and enhance driving safety.

HIGH MILEAGE PERFORMANCE AND EVEN WEAR

The shoulder tread contour (patented) allows a correct distribution of footprint contact pressure and ensures optimal even wear and the highest mileage.

STONE TRAPPING PREVENTION

Central grooves geometry optimized to promote stones ejection.

ENHANCED STEERING PRECISION

Groove and siping geometry ensures steering precision and excellent dry and wet handling.

TIRE SIZE	PRODUCT NUMBER	INTERNATIONAL LOAD INDEX SPEED CODE	LOAD RANGE PLY RATING	WEIGHT LBS (Kg)	LOADED RADIUS in. (mm)	OVERALL DIAMETER in. (mm)	OVERALL WIDTH in. (mm)	APPROVED RIMS in.	MINIMUM DUAL SPACING in. (mm)	REVS PER MILE rpm (rpk)	TREAD DEPTH 32nds (mm)	MAX SPEED mph (kph)	MAX TIRE LOAD		M+S	SMART WAY	
													SINGLE lbs. psi (kg kPa)	DUAL lbs. psi (kg kPa)			
295/80 R 22.5	6002607	154/149 M	J/18	144.8 (65.7)	19.4 (493)	41.7 (1058)	11.9 (303)	<u>9.00</u> 8.25	13.2 335	498 (310)	22/32 (17.5)	81 (130)	8270/123 (3750/850)	7160/123 (3250/850)			

Note: Rim underlined is measuring rim / Exceeding the lawful speed limit is neither recommended nor endorsed.