

H89 EVO DRIVE

NEW

SATTTM
Spiral Advanced Technology for Truck



The perfect balance between fuel efficiency and high mileage for long haul service.



EXCELLENT PERFORMANCE IN ALL WEATHER CONDITIONS

Longitudinal and transversal groove geometry as well as casing dimensioning provide excellent grip and traction in braking and acceleration throughout the life of the tire.

FUEL EFFICIENCY AND DURABILITY

New tread and base compounds deliver low rolling resistance and low heat generation, ensuring excellent retreadability and compliance with EPA SmartWay® requirements.

OUTSTANDING PRECISION AND DRIVING COMFORT

The optimized tread pattern geometry together with tread compound properties ensure uniform wear and comfortable handling.

HIGH MILEAGE

Tire profile and the particular shoulder design prevent impact damage allowing a uniform distribution of torque across the footprint, resulting in even wear and long tread life.

TIRE SIZE	PRODUCT NUMBER	INTERNATIONAL LOAD INDEX SPEED CODE	LOAD RANGE PLY RATING	WEIGHT LBS (Kg)	LOADED RADIUS in. (mm)	OVERALL DIAMETER in. (mm)	OVERALL WIDTH in. (mm)	APPROVED RIMS in.	MINIMUM DUAL SPACING in. (mm)	REVS PER MILE rpm (rpkm)	TREAD DEPTH 32nds (mm)	MAX SPEED mph (kph)	MAX TIRE LOAD		M+S	SMART WAY	
													SINGLE lbs. psi (kg kPa)	DUAL lbs. psi (kg kPa)			
295/75 R 22.5	6044000	144/141 L	G/14	137.8 (62.5)	19.0 (482)	40.7 (1034)	11.8 (300)	<u>9.00</u> 8.25	13.2 (335)	510 (317)	26/32 (20.5)	75 (120)	6175/110 (2800/760)	5675/110 (2575/760)	✓	✓	✓
11 R 22.5	6048200	144/142 L	G/14	142.4 (64.6)	19.4 (492)	41.8 (1062)	11.5 (293)	<u>8.25</u> 7.50	12.5 (318)	500 (311)	26/32 (20.5)	75 (120)	6175/105 (2800/725)	5840/105 (2650/725)	✓	✓	✓

Note: Rim underlined is measuring rim / Exceeding the lawful speed limit is neither recommended nor endorsed.