

# ANTEO PRO - D

## REGIONAL CLOSED-SHOULDER DRIVE



M+S

ANTEO



| SIZE        | PRODUCT NUMBER | LOAD RANGE<br>PLY RATING | LOADED RADIUS<br>in (mm) | OVERALL DIAMETER<br>in (mm) | OVERALL WIDTH<br>in (mm) | APPROVED RIMS<br>in. | MINIMUM DUAL SPACING<br>in. (mm) | REVS PER MILE rpm (rpk) | TREAD DEPTH<br>32nds (mm) | MAX SPEED<br>mph (kph) | SINGLE lbs<br>Psi (kg kPa) | DUAL lbs<br>Psi (kg kPa) |
|-------------|----------------|--------------------------|--------------------------|-----------------------------|--------------------------|----------------------|----------------------------------|-------------------------|---------------------------|------------------------|----------------------------|--------------------------|
| 295/75R22.5 | 6079800        | H/16                     | 19.0                     | 40.6                        | 11.3                     | <u>9.00</u>          | 13.2                             | 511                     | 29/32                     | 75                     | 7160/123                   | 6610/123                 |
|             |                |                          | (481)                    | (1032)                      | (287)                    | 8.25                 | (335)                            | (318)                   | (23)                      | (120)                  | (3250/850)                 | (3000/850)               |
| 11R22.5     | 6080000        | H/16                     | 19.5                     | 42.1                        | 11.0                     | <u>8.25</u>          | 12.5                             | 497                     | 29/32                     | 75                     | 6610/120                   | 6005/120                 |
|             |                |                          | (495)                    | (1069)                      | (280)                    | 7.50                 | (318)                            | (309)                   | (23)                      | (120)                  | (3000/825)                 | (2725/825)               |
| 11R24.5     | 6080200        | H/16                     | 20.5                     | 44.1                        | 11.2                     | <u>8.25</u>          | 12.5                             | 475                     | 29/32                     | 75                     | 7160/120                   | 6610/120                 |
|             |                |                          | (520)                    | (1119)                      | (284)                    | 7.50                 | (318)                            | (295)                   | (23)                      | (120)                  | (3250/825)                 | (3000/825)               |

Note: Rim underlined is measuring rim / Exceeding the lawful speed limit is neither recommended nor endorsed.

- Waved grooves, bumpers in the transversal grooves and tie-bar on the shoulders enhance traction and even wear.
- Functional sipes enhance wet and snow grip performance.
- Optimized tread block design promotes regular wear and tear resistance.
- Closed Shoulders promote optimized tread wear

## TRUCK TIRE COMPARISON CHART

| APPLICATION | WHEEL POSITION | DOUBLE COIN | SAILUN    | ROADMASTER TIRES |
|-------------|----------------|-------------|-----------|------------------|
| REGIONAL    | Drive          | RLB400      | SDL70 EFT | RM254            |

ANTEO