



ANTEO MOVER - D

ON-OFF ROAD
DRIVE



M+S

ANTEO



SIZE	PRODUCT NUMBER	LOAD RANGE PLY RATING	LOADED RADIUS in (mm)	OVERALL DIAMETER in (mm)	OVERALL WIDTH in (mm)	APPROVED RIMS in.	MINIMUM DUAL SPACING in. (mm)	REVS PER MILE rpm (rpkm)	TREAD DEPTH 32nds (mm)	MAX SPEED mph (kph)	SINGLE lbs Psi (kg kPa)	DUAL lbs Psi (kg kPa)
11R22.5	6080400	H/16	19.5	42.1	11.0	<u>8.25</u>	12.5	497	30/32	68	6610/120	6005/120
			(495)	(1069)	(280)	7.50	(318)	(309)	(23.5)	(110)	(3000/825)	(2725/825)
11R24.5	6080600	H/16	20.5	44.0	11.2	<u>8.25</u>	12.5	475	30/32	68	7160/120	6610/120
			(520)	(1119)	(284)	7.50	(318)	(295)	(23.5)	(110)	(3250/825)	(3000/825)

Note: Rim underlined is measuring rim / Exceeding the lawful speed limit is neither recommended nor endorsed.

- «Helix shape» tread pattern design maximizes traction in both on-road and off-road conditions.
- Multiple height bars balance wear and traction through all tire life.
- Central line blocks design improves traction
- Groove bottom redesigned protection avoids stone damage.

TRUCK TIRE COMPARISON CHART

APPLICATION	WHEEL POSITION	DOUBLE COIN	SAILUN	ROADMASTER TIRES
MIXED SERVICE	Drive	RLB600	S758	RM300 HH

ANTEO