

D79

Regional Drive Open Shoulder



TREAD A



TREAD B

- Deep lug tread design delivers outstanding traction in all weather conditions and high mileage
- High Scrub tread compound provide excellent performance in all regional service conditions
- Excellent casing durability ensures great retreadability

AVAILABLE RANGE

											MAX TIRE LOAD		M+S
TIRE SIZE	PRODUCT NUMBER	LOAD RANGE PLY RATING	LOADED RADIUS IN. (MM)	OVERALL DIAMETER IN. (MM)	OVERALL WIDTH IN. (MM)	APPROVED RIMS IN.	MINIMUM DUAL SPACING IN. (MM)	REVS PER MILE RPM(RPK)	TREAD DEPTH 32NDS (MM)	MAX SPEED MPH (KPH)*	SINGLE LBS. / PSI (KG / kPa)	DUAL LBS. / PSI (KG / kPa)	
295/75 R22.5 TREAD A	3848400	H/16	19.0	40.9	11.0	8.25, 9.00	13.2	508	28/32	81	7160/123	6610/123	✓
			(483)	(1040)	(280)		(335)	(317)	(22.5)	(130)	(3250/850)	(3000/850)	
11R22.5 TREAD B	3848600	H/16	19.6	42.1	11.5	8.25, 7.50	12.5	494	28/32	81	6610/120	6005/120	✓
			(497)	(1069)	(293)		(318)	(309)	(22.5)	(130)	(3000/825)	(2725/825)	
11R24.5 TREAD A	3848800	H/16	20.5	43.9	11.2	8.25, 7.50	12.5	472	27/32	81	7160/120	6610/120	✓
			(521)	(1116)	(285)		(318)	(295)	(21.5)	(130)	(3250/825)	(3000/825)	

*Exceeding the lawful speed limit is neither recommended nor endorsed.



NEXTROAD™